

## Application

**ATF IID** is recommended for automatic or semi-automatic transmissions and torque converters of passenger cars, light commercial vehicles, and industrial vehicles, when the manufacturer requires an Automatic Transmission Fluid (ATF) GM DEXRON® IID.

**ATF IID** is also recommended for hydrostatic transmissions, power steering applications.

**ATF IID** is also recommended for hydraulic systems when a fluid type GM DEXRON® IID is required.

## Properties

- Outstanding thermal stability in operation
- Very high viscosity index
- Excellent resistance to oxidation
- Excellent friction properties specific to the requirements of GENERAL MOTORS Hydramatic
- Excellent corrosion protection

## Approvals

GM DEXRON® IID  
FORD MERCON  
ALLISON C4

## Specifications

Specifications	Unit	Test method	Results
Color	-	ASTM D1500	Red
Foam Test II Stage (Tend./Stab.)	mL	ASTM D892	0/0
Density at 15°C	kg/m <sup>3</sup>	ASTM D4052	847
Kinematic Viscosity at 40°C	mm <sup>2</sup> /s	ASTM D445	36.04
Kinematic Viscosity at 100°C	mm <sup>2</sup> /s	ASTM D445	6.808
Viscosity Index	-	ASTM D2270	154
Pour Point	°C	ASTM D97	-42
Flash Point	°C	ASTM D92	208

\*The features mentioned above are average values obtained with some variability in production and do not constitute a specification