

## Application

**TECHNOL TRACTOR TRANSMISSION OIL** has been especially developed for transmissions with wet brakes requiring an API: GL-4 lubricant with a 10W-30 or 80W viscosity grade, in both Off-Road and On-Road vehicles. This lubricant is also perfectly adapted to automatic transmissions, torque converters and hydrostatic transmissions and more generally to any transmissions requiring an UTTO (Universal Tractor Transmissions Oil) lubricant.

**TECHNOL TRACTOR TRANSMISSION OIL** is also designed to lubricate hydraulic systems, power-assisted steering and power-take-offs (PTO) with wet clutches.

## Properties

- **TECHNOL TRACTOR TRANSMISSION OIL** is adapted to a wide range of agricultural and public works equipment and helps to reduce the stock and the number of lubricants.
- This lubricants shows excellent low temperature performances (protects friction brakes against sticking) and high temperature performances (protects against judder or excessive slip).
- **TECHNOL TRACTOR TRANSMISSION OIL** has very good extreme pressure and anti-wear properties giving optimum protection of gears and hydraulic components.

## Approvals

API: GL-4  
 MASSEY F CMS M1141/M1135  
 MASSEY F CMS M1145/M1143  
 VALTRA G2-08  
 JOHN DEERE: JDM J20C/JDM J21A  
 JASE MS 1206/1207/1209  
 NEW HOLLAND: NH 410B/NH 410C  
 CNH MAT 3505/3509/3525/3526

VOLVO CE WB101  
 ZF TE ML 03E/05F/06P/17E/21F  
 FORD: M2C 134D/FNHA 2C 201.00  
 KUBOTA UTD  
 KOMATSU AXO 80  
 MC CORMICK HTX  
 AGCO/ALLIS 821 XL CLASS  
 RENAULT: AGRICULTURE CAT TO 2

## Specifications

Specifications	Unit	Test method	Results
Density at 15°C	kg/m <sup>3</sup>	ASTM D4052	880
Kinematic Viscosity at 40°C	mm <sup>2</sup> /s	ASTM D445	64
Kinematic Viscosity at 100°C	mm <sup>2</sup> /s	ASTM D445	10.4
Viscosity Index	-	ASTM D2270	150
Pour Point	°C	ASTM D97	-39

\*The features mentioned above are average values obtained with some variability in production and do not constitute a specification