

Application

TECHNOL TURBODIESEL 10W-40 is a synthetic technology engine oil that has been developed to cover the most stringent requirements of both gasoline and diesel engines.

TECHNOL TURBODIESEL 10W-40 is particularly suited to turbocharged and multi-valve engines.

TECHNOL TURBODIESEL 10W-40 is perfectly adapted to vehicles equipped with catalysts and using unleaded fuel or liquefied petroleum gas. Also adapted to diesel and bio-diesel.

TECHNOL TURBODIESEL 10W-40 is perfectly suited to normal driving conditions.

Properties

- **Manufacturers standards:** **TECHNOL TURBODIESEL 10W-40** satisfies rigorous manufacturers standards (see above), while guaranteeing perfect and constant quality.
- **Resistance to Oxidation:** thanks to the good quality of its base oils and additives, **TECHNOL TURBODIESEL 10W-40** provides a specific resistance to oxidation.
- **Engine protection and cleanliness:** this oil ensures good engine cleanliness , reducing particle accumulation in the motor via efficient dispersant power.
- **Long-term wear Protection:** long-term wear protection of engine parts (distribution, ring, plunger and liner) increasing engine life.

Approvals

API: CF

ACEA: A3/B4

Specifications

Specifications	Unit	Test method	Results
Density at 15°C	kg/m ³	ASTM D4052	889
Kinematic Viscosity at 40°C	mm ² /s	ASTM D445	102.6
Kinematic Viscosity at 100°C	mm ² /s	ASTM D445	14.5
Viscosity Index	-	ASTM D2270	146
Pour Point	°C	ASTM D97	-36
Flash Point	°C	ASTM D92	230
Total Base Number	mgKOH/mg	ASTM D2896	6.5

*The features mentioned above are average values obtained with some variability in production and do not constitute a specification