

Application

TECHNOL STORM 15W-40 is suitable for previous generation used in both gasoline and diesel engines (passenger cars and light industrial vehicles).

TECHNOL STORM 15W-40 is adapted to vehicles equipped with catalysts and using unleaded fuel.

TECHNOL STORM 15W-40 can be used for all journey types (in towns, as well as on major roads and motorways), and is especially suitable for the most demanding service conditions.

Properties

- The outstanding thermal stability and resistance to oxidation of this oil prevent any degradation, even in extreme usage conditions.
- Exceptional anti-wear and anticorrosion properties
- This oil contains detergent and dispersive additives that keep the engine clean and thus preserve its power.

Approvals

API: SF/CF

Specifications

Specifications	Unit	Test method	Results
Density at 15°C	kg/m ³	ASTM D4052	905.8
Kinematic Viscosity at 40°C	mm ² /s	ASTM D445	132
Kinematic Viscosity at 100°C	mm ² /s	ASTM D445	15.5
Viscosity Index	-	ASTM D2270	121
Pour Point	°C	ASTM D97	-32
Flash Point	°C	ASTM D92	224
Total Base Number	mgKOH/mg	ASTM D2896	5.5

*The features mentioned above are average values obtained with some variability in production and do not constitute a specification