

## Application

**TECHNOL TURBODIESEL 15W-40** has been developed to cover the most stringent requirements of both gasoline and diesel engines\* (passenger cars and light industrial vehicles).

**TECHNOL TURBODIESEL 15W-40** is particularly suited to turbocharged and multi-valve engines.

**TECHNOL TURBODIESEL 15W-40** is perfectly adapted to vehicles equipped with catalysts and using unleaded fuel or liquefied petroleum gas.

**TECHNOL TURBODIESEL 15W-40** can be used in all operating conditions (city traffic, road, motorways), whatever the season.

## Properties

- **Manufacturers Standards:** **TECHNOL TURBODIESEL 15W-40** satisfies rigorous manufacturers standards (see above), while guaranteeing perfect and constant quality.
- **Resistance to Oxidation:** thanks to very good anti-oxidant, anti-rust, anti-foaming properties, **TECHNOL TURBODIESEL 15W-40** provides a specific resistance to oxidation.
- **Engine protection and cleanliness:** this oil ensures good engine cleanliness thanks to very high antiwear and anticorrosion properties.
- **Viscosity:** **TECHNOL TURBODIESEL 15W-40** has a high viscosity index and an excellent viscosity stability.

## Approvals

API: CF

ACEA: A3/B4

## Specifications

Specifications	Unit	Test method	Results
Density at 15°C	kg/m <sup>3</sup>	ASTM D4052	903.5
Kinematic Viscosity at 40°C	mm <sup>2</sup> /s	ASTM D445	130.1
Kinematic Viscosity at 100°C	mm <sup>2</sup> /s	ASTM D445	15.5
Viscosity Index	-	ASTM D2270	124
Pour Point	°C	ASTM D97	-32
Flash Point	°C	ASTM D92	230
Total Base Number	mgKOH/mg	ASTM D2896	6.1

\*The features mentioned above are average values obtained with some variability in production and do not constitute a specification