

## Application

**TECHNOL HYBRID 5W-30** is a fully synthetic engine oil specifically formulated for use in hybrid vehicles. This engine oil delivers outstanding fuel economy and performance under most demanding operating conditions, thanks to its high-quality base oils and additives. It provides excellent protection against corrosion, deposit, and foam formation, contains detergents and dispersants that keep the engine clean and delivers strong resistance to thermal breakdown and oxidation. It's very stable viscosity index ensures excellent lubrication of the moving components of the engine and protects it against wear and tear at low and high temperatures all year round.

## Properties

- Advanced anti-wear additives extend engine life and maintain the efficiency of vehicle systems.
- Improved deposit control prevents premature oil degradation.
- Excellent water resistance and separability prevents the formation of carbon deposits.

## Approvals

API SN

ILSAC GF-5

MEETS THE REQUIREMENTS OF GM DEXOS1 GEN2.

## Specifications

Specifications	Unit	Test method	Results
Density at 15°C	kg/m <sup>3</sup>	ASTM D4052	849
Kinematic Viscosity at 40°C	mm <sup>2</sup> /s	ASTM D445	72.6
Kinematic Viscosity at 100°C	mm <sup>2</sup> /s	ASTM D445	12.2
Viscosity Index	-	ASTM D2270	166
Flash Point	°C	ASTM D92	228
Pour Point	°C	ASTM D97	-39
Total Base Number	mgKOH/mg	ASTM D2896	9.2

\*The features mentioned above are average values obtained with some variability in production and do not constitute a specification