



**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006

---

**TECHNOL KALSEDON EP 100**

Date of the previous version: 2016-10-28

<b>Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING</b>
--

**1.1. Product identifier**

Product name	TECHNOL KALSEDON EP 100
Number	
Substance/mixture	Mixture

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Identified uses	Industrial gear oil.
-----------------	----------------------

**1.3. Details of the supplier of the safety data sheet**

Supplier	TECHNOİL LLC A. Racabli 33, Door 4 (Esra plaza) Azerbaijan, Baku Tel: +99412 404 40 44 E-mail Address: info@technol.az
----------	--



## TECHNOL KALSEDON EP 100

### Section 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

REGULATION (EC) No 1272/2008

For the full text of the H-Statements mentioned in this Section, see Section 2.2.

##### Classification

The product is not classified as dangerous according to Regulation (EC) No. 1272/2008

#### 2.2. Label elements

Labelled according to REGULATION (EC) No 1272/2008

##### Hazard Statements

None

##### Precautionary statements

None

##### Supplemental Hazard Statements

EUH210 - Safety data sheet available on request

Contains Amines, C12-14-tert-alkyl. May produce an allergic reaction

#### 2.3. Other hazards

Physical-Chemical Properties Contaminated surfaces will be extremely slippery.

Environmental properties Should not be released into the environment.

### Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.2. Mixture

##### Hazardous components

Chemical Name	EC-No	REACH Registration Number	CAS-No	Weight %	GHS Classification
Amines, C12-14-tert-alkyl	273-279-1	01-2119456798-18	68955-53-3	0.1-0.24	Skin Corr. 1B (H314) Skin Sens. 1A (H317) Acute Tox. 4 (H302) Acute Tox. 3 (H311) Acute Tox. 2 (H330) STOT SE 3 (H335) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)

Additional information Product containing mineral oil with less than 3% DMSO extract as measured by IP 346.

## TECHNOL KALSEDON EP 100

For the full text of the H-Statements mentioned in this Section, see Section 16.

### Section 4: FIRST AID MEASURES

#### **4.1. Description of first aid measures**

General advice	IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.
Eye contact	Rinse thoroughly with plenty of water, also under the eyelids.
Skin contact	Remove contaminated clothing and shoes. Wash off with soap and water. Wash contaminated clothing before reuse.
Inhalation	Move to fresh air.
Ingestion	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control centre immediately.

#### **4.2. Most important symptoms and effects, both acute and delayed**

Eye contact	Not classified.
Skin contact	Not classified. May produce an allergic reaction.
Inhalation	Not classified. Inhalation of vapours in high concentration may cause irritation of respiratory system.
Ingestion	Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

#### **4.3. Indication of immediate medical attention and special treatment needed, if necessary**

Notes to physician	Treat symptomatically.
--------------------	------------------------

### Section 5: FIRE-FIGHTING MEASURES

#### **5.1. Extinguishing media**

Suitable extinguishing media	Carbon dioxide (CO <sub>2</sub> ). ABC powder. Foam. Water spray or fog.
Unsuitable Extinguishing Media	Do not use a solid water stream as it may scatter and spread fire.

#### **5.2. Special hazards arising from the substance or mixture**

Special hazard	Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration.
----------------	--

#### **5.3. Precautions for fire-fighters**



## TECHNOL KALSEDON EP 100

### Special protective equipment for fire-fighters

Wear self-contained breathing apparatus and protective suit.

### Other information

Cool containers / tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

## Section 6: ACCIDENTAL RELEASE MEASURES

### **6.1. Personal precautions, protective equipment and emergency procedures**

#### General Information

Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

### **6.2. Environmental precautions**

#### General Information

Do not allow material to contaminate ground water system. Try to prevent the material from entering drains or water courses. Local authorities should be advised if significant spillages cannot be contained.

### **6.3. Methods and materials for containment and cleaning up**

#### Methods for cleaning up

Dam up. Contain spillage, and then collect with non-combustable absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

### **6.4. Reference to other sections**

#### Personal protective equipment

See Section 8 for more detail.

#### Waste treatment

See section 13.

## Section 7: HANDLING AND STORAGE

### **7.1. Precautions for safe handling**

#### Advice on safe handling

When using, do not eat, drink or smoke. For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapours or spray mist. Avoid contact with skin, eyes and clothing.

#### Prevention of fire and explosion

Take precautionary measures against static discharges: Ground/bond containers, tanks and transfer/receiving equipment.

#### Hygiene measures

Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets.

## TECHNOL KALSEDON EP 100

### 7.2. Conditions for safe storage, including any incompatibilities

#### Technical measures/Storage conditions

Keep away from food, drink and animal feedingstuffs. Keep in a bunded area. Keep container tightly closed. Preferably keep in the original container. Otherwise, reproduce all the statutory information from the labels onto the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Protect from frost, heat and sunlight. Protect from moisture.

#### Materials to avoid

Strong oxidising agents.

### 7.3. Specific use(s)

#### Specific use(s)

No information available.

## Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

### 8.1. Control parametres

#### Exposure limits

Mineral oil mist:

USA: OSHA (PEL) TWA 5 mg/m<sup>3</sup>, NIOSH (REL) TWA 5 mg/m<sup>3</sup>, STEL 10 mg/m<sup>3</sup>, ACGIH (TLV) TWA 5 mg/m<sup>3</sup> (highly refined)

#### Legend

See section 16

#### DNEL Worker (Industrial/Professional)

Chemical Name	Short term, systemic effects	Short term, local effects	Long term, systemic effects	Long term, local effects
Amines, C12-14-tert-alkyl 68955-53-3			12.5 mg/m <sup>3</sup> Inhalation	12.1 mg/m <sup>3</sup> Inhalation

#### DNEL Consumer

Chemical Name	Short term, systemic effects	Short term, local effects	Long term, systemic effects	Long term, local effects
Amines, C12-14-tert-alkyl 68955-53-3			2.5 mg/m <sup>3</sup> Inhalation 0.35 mg/kg bw/day Oral	1.2 mg/m <sup>3</sup> Inhalation

#### Predicted No Effect Concentration (PNEC)

Chemical Name	Water	Sediment	Soil	Air	STP	Oral
Amines, C12-14-tert-alkyl 68955-53-3	0.001 mg/L fw 0.0001 mg/l mw 0.004 mg/l or	2.14 mg/kg dw fw 0.214 mg/kg dw mw	0.428 mg/kg dw		0.635 mg/l	4.71 mg/kg

### 8.2. Exposure controls

#### Occupational Exposure Controls

#### Engineering measures

Apply technical measures to comply with the occupational exposure limits. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.

## TECHNOL KALSEDON EP 100

### Personal protective equipment

<b>General Information</b>	If the product is used in mixtures, it is recommended that you contact the appropriate protective equipment suppliers. These recommendations apply to the product as supplied.
<b>Respiratory protection</b>	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Respirator with combination filter for vapour/particulate (EN 14387). Type A/P1. The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses.
<b>Eye protection</b>	If splashes are likely to occur, wear:.. Safety glasses with side-shields.
<b>Skin and body protection</b>	Wear suitable protective clothing. Protective shoes or boots. Long sleeved clothing.
<b>Hand protection</b>	Hydrocarbon-proof gloves: Fluorinated rubber. Nitrile rubber. In case of prolonged contact with the product, it is recommended to wear gloves complying with EN 420 and EN 374 standards, protecting at least for 480 minutes and having a thickness of 0,38 mm at least. These values are indicative only. The level of protection is provided by the material of the glove, its technical characteristics, its resistance to the chemicals to be handled, the appropriateness of its use and its replacement frequency.

### Environmental exposure controls

<b>General Information</b>	The product should not be allowed to enter drains, water courses or the soil.
----------------------------	---

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Appearance	Clear		
Colour	yellow to amber		
Physical state @20°C	Liquid		
Odour	characteristic		
Odour Threshold	No information available		
<b><u>Property</u></b>	<b><u>Values</u></b>	<b><u>Remarks</u></b>	<b><u>Method</u></b>
pH		Not applicable	
Melting point/range		Not applicable	
Boiling point/boiling range		No information available	
Flash point	212 °C		ISO 2592 ISO 2592
Evaporation rate		No information available	
Flammability Limits in Air		No information available	
Upper		No information available	
Lower		No information available	
Vapour pressure		No information available	
Vapour density		No information available	
Relative density	0.88	@ 15 °C	ISO 3675

## TECHNOL KALSEDON EP 100

Density	888 kg/m <sup>3</sup>	@ 15 °C	ISO 3675
Water solubility		Insoluble	
Solubility in other solvents		Soluble in many common organic solvents	
logPow		No information available	
Autoignition temperature		No information available	
Decomposition temperature		No information available	
Viscosity, kinematic	100 mm <sup>2</sup> /s	@ 40 °C	ISO 3104
	11.3 mm <sup>2</sup> /s	@ 100 °C	ISO 3104
Explosive properties	Not explosive		
Oxidising properties	Not applicable		
Possibility of hazardous reactions	No information available		

### 9.2. Other information

Freezing point No information available

Pour point -28 °C ISO 3106

## Section 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

General Information No information available.

### 10.2. Chemical stability

Stability Stable under recommended storage conditions.

### 10.3. Possibility of hazardous reactions

Hazardous reactions None under normal processing.

### 10.4. Conditions to Avoid

Conditions to Avoid Heat (temperatures above flash point), sparks, ignition points, flames, static electricity.

### 10.5. Incompatible materials

Materials to avoid Strong oxidising agents.

### 10.6. Hazardous Decomposition Products

Hazardous Decomposition Products None under normal use.

## Section 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

Acute toxicity Local effects Product Information



## TECHNOL KALSEDON EP 100

<b>Skin contact</b>	. Not classified. May produce an allergic reaction.
<b>Eye contact</b>	. Not classified.
<b>Inhalation</b>	. Not classified. Inhalation of vapours in high concentration may cause irritation of respiratory system.
<b>Ingestion</b>	. Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

### Acute toxicity - Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Amines, C12-14-tert-alkyl	LD50 612 mg/kg (Rat)	LD50 251 mg/kg (Rabbit)	LC50 (4h) 157 ppm (Rat - gas)

### Sensitisation

**Sensitisation** Not classified as a sensitizer. Contains sensitizer(s). May produce an allergic reaction.

### Specific effects

**Carcinogenicity** This product is not classified carcinogenic.  
**Mutagenicity** This product is not classified as mutagenic.  
**Reproductive toxicity** This product does not present any known or suspected reproductive hazards.

### Repeated Dose Toxicity

**Subchronic Toxicity** No information available.

### Target Organ Effects (STOT)

### Other information

**Other adverse effects** Characteristic skin lesions (oil blisters) may develop following prolonged and repeated exposures (contact with contaminated clothing).

## **Section 12: ECOLOGICAL INFORMATION**

### **12.1. Toxicity**

Not classified.

### Acute aquatic toxicity - Product Information

No experimental data available .

### Acute aquatic toxicity - Component Information





## TECHNOL GEAR OIL CLP 100

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates.	Toxicity to fish	Toxicity to microorganisms
Amines, C12-14-tert-alkyl 68955-53-3	EC50 (72h) 0.44 mg/l (Algae)	EC50 (48h) 2.5 mg/l (Daphnia magna)	LC50 (96h) 1.3 mg/l (Fish)	

### Chronic aquatic toxicity - Product Information

No information available.

### Chronic aquatic toxicity - Component Information

No information available.

### Effects on terrestrial organisms

No information available.

## **12.2. Persistence and Degradability**

### **General Information**

No information available.

## **12.3. Bioaccumulative potential**

### **Product Information**

No information available.

### **logPow**

No information available

### **Component Information**

Chemical Name	log Pow
Amines, C12-14-tert-alkyl - 68955-53-3	2.9

## **12.4. Mobility in soil**

### **Soil**

Given its physical and chemical characteristics, the product generally shows low soil mobility.

### **Air**

Loss by evaporation is limited.

### **Water**

Insoluble. The product spreads on the surface of the water.

## **12.5. Results of PBT and vPvB assessment**

### **PBT and vPvB assessment**

.

## **12.6. Other adverse effects**

### **General Information**

No information available.

## **Section 13: DISPOSAL CONSIDERATIONS**

### **13.1. Waste treatment methods**

## TECHNOL KALSEDON EP 100

**Waste from residues / unused products** Dispose of in accordance with the European Directives on waste and hazardous waste. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations.

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

**EWC Waste Disposal No** The following Waste Codes are only suggestions: 13 02 05. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used.

### Section 14: TRANSPORT INFORMATION

**ADR/RID** not regulated

**IMDG/IMO** not regulated

**ICAO/IATA** not regulated

**ADN** not regulated

### Section 15: REGULATORY INFORMATION

#### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

88/379/EEC (Classification and Labelling):

Symbols:

Xn Harmful

R Phrases:

R22 Harmful if swallowed.

R36/38 Irritating to eyes and skin.

S Phrases:

S2 Keep out of reach of children.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S28 After contact with skin, wash immediately with plenty of... (to be specified by the manufacturer).

Special Provisions:

EC label.

Contents:

2,4,6-tris(dimethylaminomethyl)phenol

Where applicable, refer to the following regulatory provisions :

Directive 82/501/EEC ('Activities linked to risks of serious accidents') and subsequent amendments.

## TECHNOL KALSEDON EP 100

• Avoid exceeding occupational exposure limits (see section 8).

### Section 16: OTHER INFORMATION

#### Full text of H-Statements referred to under sections 2 and 3

H314 - Causes severe skin burns and eye damage  
 H317 - May cause an allergic skin reaction  
 H302 - Harmful if swallowed  
 H311 - Toxic in contact with skin  
 H330 - Fatal if inhaled  
 H335 - May cause respiratory irritation  
 H400 - Very toxic to aquatic life  
 H410 - Very toxic to aquatic life with long lasting effects

#### Abbreviations, acronyms

UVCB = Substance of unknown or Variable composition, Complex reaction products or Biological material  
 OECD = Organization for Economic Co-operation and Development  
 bw = body weight  
 bw/day = body weight/day  
 GLP = Good Laboratory Practice  
 fw = fresh water  
 mw = marine water  
 or = occasional release  
 dw = dry weight  
 NIOSH = National Institute of Occupational Safety and Health  
 OSHA = Occupational Safety and Health Administration  
 ACGIH = American Conference of Governmental Industrial Hygienists  
 IARC = International Agency for Research of Cancer  
 DNEL = Derived No Effect Level  
 PNEC = Predicted No Effect Concentration  
 LD50 = 50% Lethal Dose - Chemical amount, given at once, which causes the death of 50% (one half) of a group of test animals  
 LC50 = 50% Lethal concentration - Concentration of a chemical in air or a chemical in water which causes the death of 50% (one half) of a group of test animals  
 LL = Lethal Loading  
 NOEC = No Observed Effect Concentration  
 NOEL = No Observed Effect Level  
 NOAEL = No Observed Adverse Effect Level  
 EC x = Effect Concentration associated with x% response

#### Legend Section 8

TWA: Time Weight Average

STEL: Short Time Exposure Limit

+	Sensitiser	*	Skin designation
**	Hazard Designation	C:	Carcinogen
M:	Mutagen	R:	Toxic to reproduction

#### Revision Note

\*\*\* Indicates updated section.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006



---

## TECHNOL KALSEDON EP 100

---

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of Safety Data Sheet