

Application

TECHNOL POWER 10W-30 is a high-performance synthetic lubricant, especially suitable for long-distance diesel-powered heavy-duty trucks.

TECHNOL POWER 10W-30 lubricant is recommended for Euro 5 standard engines and earlier engine models of most European and American manufacturers, especially IVECO.

Properties

- **TECHNOL POWER 10W-30** is a lubricating oil with modern technology, combining synthetic base oil with high performance additives.
- Detergent, anti-oxidant and anti-corrosion properties help achieve extended oil change intervals and reduce maintenance costs as specified by MAN, Mercedes-Benz and IVECO.
- **TECHNOL POWER 10W-30** lubricant has a very high TBN level (Total Alkalinity/16 mgKOH/g). This, in turn, neutralizes acid compounds and prevents their corrosive properties.
- High-quality detergent, disintegrant and anti-wear additives keep sensitive engine parts clean.

Approvals

API: CH-4/SJ

ACEA: 2016 E7

MB 228.3

MAN 3275

Volvo: VDS-3

RVI RLD-2

Cummins CES 20077/78

CAT ECF-2

Global DHD-1

Volvo: VDS-3

JASO DH-1

Specifications

Specifications	Unit	Test method	Results
Density at 15°C	kg/m ³	ASTM D4052	869
Kinematic Viscosity at 40°C	mm ² /s	ASTM D445	78.08
Kinematic Viscosity at 100°C	mm ² /s	ASTM D445	12.2
Viscosity Index	-	ASTM D2270	153
Pour Point	°C	ASTM D97	232
Flash Point	°C	ASTM D92	-37
Total Base Number	mgKOH/mg	ASTM D2896	10.1

*The features mentioned above are average values obtained with some variability in production and do not constitute a specification