

Application

TECHNOL MULTI-VEHICLE ATF is a high quality automatic transmission fluid formulated for automatic, semi-automatic transmissions, and torque converters of passenger, light commercial and industrial vehicles that require GM DEXRON III H or Mercon. This fluid can also be used for hydrostatic transmissions, power steering and hydraulic systems. Having a high viscosity index, this fluid provides excellent resistance to corrosion and foam formation. It also has outstanding thermal stability, antioxidant, antirust, antiwear properties and offers high-level protection under all conditions. Its excellent friction properties meeting the requirements of GENERAL MOTORS Hydramatic ensure smooth gear shifting.

Approvals

GM DEXRON® II, IID, IIIG, IIIH, VI
 FORD MERCON, MERCON LV
 MB 236.1/2/3/4/5/6/7/8/9,ZF 4HP20
 VW / Audi G-052-025-A2, G-052-162-A1/A2, G-052-990, G-052-055
 BMW 7045E, ETL8072B, LA2634, LT71141, JWS 3309 (T-IV)
 Hyundai / Kia SP-II, SP-III, SP-IV, SPH-IV, Red 1
 Toyota D-II, D-III, T-III, T-IV, WS
 Nissan Matic Fluid C, D, J, K, P, S
 Honda ATF-Z1 (except in CVTs), ATF Ultra II
 Mazda ATF D-II, M-III, M-V, FZ, F-1, S-1, N-1, 3317
 Mitsubishi Diaqueen SK, SP-II, SP-III, SP-IV, AW, J2, J3, ATF PA
 Volvo 97325, 97335, 97340, 1161521, 1161540, 1161640
 Allison C-3, C-4
 Aisin Warner JWS 3309, JWS 3324, AW-1, AW-2
 ZF TE-ML 05L, 09, 11A, 11B, 21L
 Jaso M315-2013 1A, 1A-LV, 2A

Specifications

Specifications	Unit	Test method	Results
Density at 15°C	kg/m ³	ASTM D4052	852
Kinematic Viscosity at 40°C	mm ² /s	ASTM D445	33
Kinematic Viscosity at 100°C	mm ² /s	ASTM D445	6.8
Viscosity Index	-	ASTM D2270	171
Pour Point	°C	ASTM D97	-49
Flash Point	°C	ASTM D92	215

*The features mentioned above are average values obtained with some variability in production and do not constitute a specification

Sənəd No: LAB-F 11/1 Tarix: 10.01.2018