

Application

TECHNOL ATF VI is a fully synthetic automatic transmission fluid formulated with carefully selected high quality base oils and additives to fulfil the requirements of GM DEXOS VI and Ford MERCON LV. This fluid is suitable for use in automatic transmissions, torque convertors, power steering systems, and other hydraulic devices of passenger vehicles of various manufacturers. A part from improving fuel economy, it ensures thermal stability and low temperature fluidity, exhibits outstanding resistance to oxidation and corrosion, and provides maximum protection against wear and rust, delivering significantly extended service life. It possesses excellent friction properties that help improve driving experience through smooth gear shifting performance.

Approvals

GM DEXRON® VI
 FORD MERCON LV
 MB 236.14
 CHRYSLER ATF+4
 ZF LIFEGUARDFLUID 6

HYUNDAI / KIA SP IV
 TOYOTA / LEXUS WS
 NISSAN MATIC S
 ALISSON C-4
 JASO 1A-LV

Specifications

Specifications	Unit	Test method	Results
Colour		ASTM D1500	RED
Density at 15°C	kg/m ³	ASTM D4052	850
Kinematic Viscosity at 40°C	mm ² /s	ASTM D445	29.1
Kinematic Viscosity at 100°C	mm ² /s	ASTM D445	6.1
Viscosity Index	-	ASTM D2270	164
Pour Point	°C	ASTM D97	-44
Flash Point	°C	ASTM D92	215

*The features mentioned above are average values obtained with some variability in production and do not constitute a specification

Sənəd No: LAB-F 11/1 Tarix: 10.01.2018