

Application

TECHNOL GOLD 5W-30 has been developed for all gasoline engines (multi-valve, turbocharger, with or without catalysts) and all recent diesel engines - with or without turbo for use on light passenger and commercial vehicles without particulate filters.

TECHNOL GOLD 5W-30 can be used for all journey types (in towns, as well as on major roads and motorways), and is especially suitable for the most demanding service conditions. It is suited to every driving style, especially sporty and high-speed.

TECHNOL GOLD 5W-30 has been specially designed to meet manufacturers' requirements with regard to greater intervals between oil changes.

Properties

- **Antiwear protection:** this oil ensures excellent protection, particularly against wear of the distribution system.
- **Extends engine life:** the outstanding thermal stability and resistance to oxidation of this oil prevent any degradation, even in extreme usage conditions.
- **Engine protection, cleanliness and performance:** this oil contains detergent and dispersive additives that keep the engine clean and thus preserve its power.
- **Longer intervals between oil changes:** **TECHNOL GOLD 5W-30** has been specially designed to meet manufacturers' requirements with regard to greater intervals between oil changes.

Approvals

ACEA: 2012 A5/B5
API: SL

RN0700
FORD WSSM2C: 913 C/D

Specifications

Specifications	Unit	Test method	Results
Density at 15°C	kg/m ³	ASTM D4052	851
Kinematic Viscosity at 40°C	mm ² /s	ASTM D445	55.3
Kinematic Viscosity at 100°C	mm ² /s	ASTM D445	9.9
Viscosity Index	-	ASTM D2270	167
Pour Point	°C	ASTM D97	-44
Flash Point	°C	ASTM D92	230
Total Base Number	mgKOH/mg	ASTM D2896	9.2

*The features mentioned above are average values obtained with some variability in production and do not constitute a specification