

Application

TECHNOL POWER 15W-40 is a mineral lubricant used in on-road diesel technology.

It is recommended to Euro 3, and previous engines of most European and American manufacturers. It is also adapted to Euro 5 and previous engines of some manufacturers with appropriate oil drain intervals.

TECHNOL POWER 15W-40 enables coverage some fleet of mixed brands (American and European manufacturers) with a minimal number of products.

Properties

- **TECHNOL POWER 15W-40** contains excellent viscosity stability in service, guaranteeing effective engine lubrication in severe conditions.
- Outstanding detergent, dispersant and anti-wear properties keep the engine clean and enable efficient control of soot, sludge and piston deposits.
- Piston cleanliness performance affords effective protection against cylinder liner polishing.

Approvals

API: CH-4/SJ

ACEA: E5-12

MERCEDES BENZ: MB 228.1

MAN: 3275

VOLVO: VDS-2

MAN: CAT 2

Specifications

Specifications	Unit	Test method	Results
Density at 15°C	kg/m ³	ASTM D4052	889
Kinematic Viscosity at 40°C	mm ² /s	ASTM D445	120.1
Kinematic Viscosity at 100°C	mm ² /s	ASTM D445	15.5
Viscosity Index	-	ASTM D2270	135
Pour Point	°C	ASTM D97	-33
Flash Point	°C	ASTM D92	230
Total Base Number	mgKOH/mg	ASTM D2896	7.9

*The features mentioned above are average values obtained with some variability in production and do not constitute a specification