

Application

TECHNOL POWER+ 15W-40 is a semi synthetic lubricant used in on-road diesel technology.

It is recommended to Euro 3, and previous engines of most European and American manufacturers. It is also adapted to Euro 5 and previous engines of some manufacturers with appropriate oil drain intervals.

TECHNOL POWER+ 15W-40 enables coverage some fleet of mixed brands (American and European manufacturers) with a minimal number of products.

Properties

- **TECHNOL POWER+ 15W-40** contains excellent viscosity stability in service, guaranteeing effective engine lubrication in severe conditions.
- Outstanding detergent, dispersant and anti-wear properties keep the engine clean and enable efficient control of soot, sludge and piston deposits.
- Piston cleanliness performance affords effective protection against cylinder liner polishing.

Approvals

API: CI-4/SL
 MECEDES BENZ: MB 228.3
 VOLVO: VDS 3
 RENAULT TRUCKS: RLD2
 CUMMINS: CES 20078
 JASO DH1: Level 4

ACEA: E7-12 GLOBAL DHD1
 MTU: Type 2
 MAN: M3275 – 1
 MACK: EO-N/EO-M Plus
 DETROIT DIESEL: DDC 93K215
 Allison: C4 Level

Specifications

Specifications	Unit	Test method	Results
Density at 15°C	kg/m ³	ASTM D4052	889
Kinematic Viscosity at 40°C	mm ² /s	ASTM D445	106.4
Kinematic Viscosity at 100°C	mm ² /s	ASTM D445	14.3
Viscosity Index	-	ASTM D2270	137
Pour Point	°C	ASTM D97	-34
Flash Point	°C	ASTM D92	230
Total Base Number	mgKOH/mg	ASTM D2896	10.4

*The features mentioned above are average values obtained with some variability in production and do not constitute a specification