

## Application

**TECHNOL SILVER 10W-40** is a semi-synthetic engine oil designed to meet the heavy demands of both gasoline and diesel engines. Suitable for passenger cars, light industrial vehicles, especially turbocharged engines.

This engine oil is perfectly adapted for engines with catalytic neutralizers and all types of engines using gasoline fuel.

**TECHNOL SILVER 10W-40** can be used in all seasons, in all operating conditions (urban roads, ordinary roads and highways).

## Properties

- **Manufacturers' Standards:** **TECHNOL SILVER 10W-40** meets the strictest manufacturers' requirements (above), while ensuring excellent and constant quality.
- **Oxidation resistance:** due to its strong properties against oxidation, rusting and foaming, it shows special resistance to oxidation.
- **Engine protection and cleanliness:** due to its high anti-wear and anti-corrosion properties, it ensures proper engine cleanliness.
- **Viscosity:** **TECHNOL SILVER 10W-40** has a high viscosity index and excellent viscosity stability.

## Approvals

API: SL/CF  
ACEA: A3/B4

## Specifications

Specifications	Unit	Test method	Result
Density at 15°C	kg/m <sup>3</sup>	ASTM D4052	889
Kinematic Viscosity at 40°C	mm <sup>2</sup> /s	ASTM D445	99.35
Kinematic Viscosity at 40°C	mm <sup>2</sup> /s	ASTM D445	13.9
Viscosity Index	-	ASTM D2270	142
Flash Point	°C	ASTM D92	230
Drop Point	°C	ASTM D97	-36
Total Base Number	mgKOH/mg	ASTM D2896	11.2