

Application

TECHNOL SILVER 15W-40 is a heavy-duty engine oil for both gasoline and diesel engines. Suitable for passenger cars, light industrial vehicles, especially turbocharged engines.

TECHNOL SILVER 15W-40 engine oil is perfectly adapted for engines with catalytic neutralizers and all types of engines using unleaded fuel.

TECHNOL SILVER 15W-40 can be used in all seasons, in all operating conditions (urban roads, ordinary roads and highways).

Properties

- **Manufacturers' Standards:** **TECHNOL SILVER 15W-40** meets the strictest manufacturers' requirements (above), while ensuring excellent and constant quality.
- **Oxidation resistance:** due to its strong properties against oxidation, rusting and foaming, it shows special resistance to oxidation.
- **Engine protection and cleanliness:** due to its high anti-wear and anti-corrosion properties, it ensures proper engine cleanliness.
- **Viscosity:** **TECHNOL SILVER 15W-40** has a high viscosity index and excellent viscosity stability.

Approvals

API: SJ/CF
ACEA: A3/B4

Specifications

Specifications	Unit	Test method	Result
Density at 15°C	kg/m ³	ASTM D4052	889
Kinematic Viscosity at 40°C	mm ² /s	ASTM D445	116.7
Kinematic Viscosity at 40°C	mm ² /s	ASTM D445	15.2
Viscosity Index	-	ASTM D2270	136
Flash Point	°C	ASTM D92	230
Drop Point	°C	ASTM D97	-33
Total Base Number	mgKOH/mg	ASTM D2896	9