## **TECHNOL SILVER 20W-50**



# Application ///

**TECHNOL SILVER 20W-50** is a heavy-duty engine oil for both gasoline and diesel engines. Suitable for passenger cars, light industrial vehicles, especially turbocharged engines.

**TECHNOL SILVER 20W-50** engine oil is perfectly adapted for engines with catalytic neutralizers and all types of engines using unleaded fuel.

**TECHNOL SILVER 20W-50** can be used in all seasons, in all operating conditions (urban roads, ordinary roads and highways).

#### Properties

- Manufacturers' Standards: TECHNOL SILVER 20W-50 meets the strictest manufacturers' requirements (above), while ensuring excellent and constant quality.
- Oxidation resistance: due to its strong properties against oxidation, rusting and foaming, it shows special resistance to oxidation.
- Engine protection and cleanliness: due to its high anti-wear and anti-corrosion properties, it ensures proper engine cleanliness.
- Viscosity: TECHNOL SILVER 20W-50 has a high viscosity index and excellent viscosity stability.

#### Approvals

API: SJ/CF ACEA: A3/B4

### **Specifications**

| Specifications               | Unit     | Test method | Result |
|------------------------------|----------|-------------|--------|
| Density at 15°C              | kg/m³    | ASTM D4052  | 889    |
| Kinematic Viscosity at 40°C  | mm²/s    | ASTM D445   | 181.7  |
| Kinematic Viscosity at 100°C | mm²/s    | ASTM D445   | 19.8   |
| Viscosity Index              | -        | ASTM D2270  | 126    |
| Flash Point                  | °C       | ASTM D92    | 230    |
| Drop Point                   | °C       | ASTM D97    | -30    |
| Total Base Number            | mgKOH/mg | ASTM D2896  | 7.2    |

Sənəd No: LAB-F 11/1 Tarix: 10.01.2018